



PRINCIPAL DIMENSIONS according to ISO 8666

Length Overall (Lmax)	10.31 m	33' 10"
Length Overall (Lmax) - ext. platf.	11.01 m	36' 1"
Length of Hull (LH)	10.07 m	33' 0"
Beam (BH)	3.50 m	11' 6"
Draught (Tmax)	0.94 m	3' 1"
Air height	3.45 m	11' 4"
Fuel capacity	570 I	125 UK gal
Water capacity	220	48 UK gal
Displacement	7.06 t	6.95 UK t
CE Category	В	В
Max. persons	8	8



research and development. All measurements/figures approximate. Errors and omissions are excepted. Specification and material can be changed without notice. Please check with your dealer for a full list of inclusions. Valid from 2024.07.01 for deliveries from 2025.01.01 until 2025.06.30. S20D.25.V.2024-11-12.248

^{*}Max. outboard horse power: 2x300 hp; max. speed allowed: 40 knots. SEALINE reserves the right to change specifications in line with the company policy of improvement through









MAIN DECK with extended bathing platform



LOWER DECK standard



LOWER DECK option



LOWER DECK option



HULL

- GRP hull with sandwich construction, isophthalic gelcoat, coulour: STAR WHITE, 1st layer vinyl ester resin
- Waterline, isophthalic gelcoat, colour: BLACK
- Aft pillar vinyl wrapped in GREY with SEALINE logo
- 2 hull windows not openable (bow cabin port side, lobby)
- 3 hull windows with openable porthole (aft cabin port side, bow cabin starboard side and toilet)

DECK & COCKPIT

- GRP deck with antislip surface, isophthalic gelcoat, colour: STAR WHITE, 1st layer vinyl ester resin, double anchor locker, self draining, anchor arm stainless steel
- Fender strip, rubber, colour: BLACK
- SEALINE steering wheel
- Full windscreen with pantograph wipers and screen wash
- SEALINE convertible fabric roof system in cockpit, manual
- SEALINE convertible fabric roof system at steering position, manual
- Bathing platform in fiberglass, bathing ladder with handrail and bathing shower with hot and cold water and opening stainless steel gate.
- Stainless steel pulpit, 4 stainless steel mooring cleats, stainless steel handrails
- Seating "U"-shaped bench with fixed backrest and table with fixed leg. Manual bimini.
 External galley with sink, cold and hot water, fridge, 2-burner gas stove and storage. Pilot seat plus 2 copilot seats.
- Table in cockpit with fixed leg and cover, on port side. Storage room with electric opening

PROPULSION

- Engine battery preparation including main switches
- Fuel tank, capacity: 570 litres

ELECTRICAL EQUIPMENT

- 12 V and 230 V electric system with 230 V shore power connection. Sockets in lobby (2), bow cabin (2), aft cabin (1), toilet (1) and 12V on dashboard (1)
- Batteries-Service: 2 x 160 Ah
- · Country Version: EU / AUS
- · Manual toilet
- Light in cabins and lobby with dimmer.
 Dimmable indirect lights and reading lights in cabins. Lights in toilet, cockpit and storage room
- Holding tank (85 I)
- Water tank (220 I) with gauge and fresh water pump
- Bilge pumps: automatic electric (2) and manual emergency bilge pump in cockpit (1)

NAVIGATION & INSTRUMENTS

- · Standard dashboard
- Compass
- Navigation lights

LAYOUT & INTERIOR

- A1: Bow cabin with double berth, 1 wardrobe, drawers underneath the bed, various lockers and storage boxes. 3 skylights, one openable.
 Fully equipped head with separated shower stall, handheld shower and comfort seat.
 Manual toilet. Open bulkhead.
- B1: Lobby with storage furniture and hanging lockers
- C1: Aft cabin with double berth, 1 wardrobe and storage

UPHOLSTERY & WOOD

- · Heads flooring wood style
- Exterior seating material and upholstery helmsman seat in SARDINIA, colour: GULL WING (according to colour card).
- · Standard mattresses in all cabins
- Interior furniture in high quality marine plywood: MADISON WOOD (according to colour card).
 Bedheads in bow cabin in MADISON WOOD (according to colour card) and aft cabin in soft material.
- Floorboard lower deck AUSTRALIAN ACACIA (according to colour card)

TRANSPORT

SEALINE Owner's Manual in SEALINE document bag